



**SPECIFICATIONS**    CT240-1200D    CT320-1200D    CT400-1200D

Flow Rate			
Gallons per Minute	240	320	400
Tank Capacity			
Gallons	300	300	300
Drag Out Capacity			
Gallons	900	900	900
Inlet Height			
Inches/mm	36/910	36/910	36/910
Cyclone Pump			
Horsepower	10	15	15
Clean Coolant Pump			
Horsepower	5	7.5	7.5
Conveyor Motor			
Horsepower	1/2	1/2	1/2
Number of Cyclones in System	12	16	20

**COMPONENT SPECIFICATIONS**

**Piping:** All piping schedule 40 black iron.

**Sheet Metal:** 1/4 inch hot rolled steel.

**Painting:** Two part epoxy primer and finish coat, any color specified.

**Gages:** Inlet 0-60 PSI, outlet 0-30 PSI.

**Cyclone Pump:** Cast iron with centrifugal impeller.

**Clean Coolant Pump:** Rated flow up to 25 PSI.

**Electric Motors:** TEFC for 230/460/3/60 Hz. operation.

**Electrical Controls:** NEMA 12 enclosure with AC magnetic starters, start and stop buttons, indicator lights, 115 volt single phase control circuit, fused disconnect switch.

Special systems designed to specifications.

Specifications are subject to change without prior notice.